



V2 Double-heads High Resolution Inkjet Printer



Parameters

Specification	Controller: 225*140*36mm (H*W*D) / 8.9*5.5*1.4 inch Printhead: 175*52*33mm (H*W*D) / 6.9*2.0*1.3 inch
Language	Chinese, English, Japanese, French, German, Spanish, Portuguese and Russian
Resolution	300DPI
Counters	Can be set in Series No, Carton No, Pallet No, etc
Printable heights (mm)	1~25.4mm
Printing speed	0-60 m/min(300 DPI) 0-30 m/min(600 DPI)
Conveyor speed	Can be set, auto-calculated or use external synchronizer
Barcode	UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, EAN128, PDF417, DATAMATRIX, QR
Date format	Different options, also can user define
Screen	8 inch, 1280 *720 resolution capacitive screen
Ink management	Identify ink type automatically and use the best printing parameters Original HP ink cartridge guaranteed Automatic measuring system for ink consumption
Installation	Standard side printing, down printing bracket and anti-shock bracket, users can install according to their needs; spring mechanism is optional
Power Input	AC 100V-240V/50-60HZ, 200VA
Power Output	30VDC 3A
Certificate	CE, FCC



Variable Data

Support dynamic data, database printing.



Maximum Printable Height 1"

Support dynamic data, database printing.



Independent Controller

8 inch colorful LCD capacitive screen, brand new interface, can connect with normal or curve surface printhead.



Independent Printhead

Printheads are separated from the controller, multi-combinations, easy operation.